



Recommended sealer...  
\$ 220.00 per 20L drum, incl. GST

**WATTYL** PaintWorks®

Data Sheet D9.31

## PROFESSIONAL CHOICE™ Concrete & Stencil Clear

Page 1 of 2  
Resource Code 139501  
March 2010

### DESCRIPTION

- Watty Professional Choice™ Concrete & Stencil Clear is a premium quality heavy duty clear finish designed to protect and enhance stencilled concrete, faux brick and pebble finishes around the home.

### PRINCIPAL CHARACTERISTICS

- Suitable for interior or exterior use.
- Forms an impervious layer to resist penetration from spillage such as oil, grease and food.
- Provides an attractive and durable finish.
- Helps seal exposed aggregate and pebblecrete surfaces, whilst protecting masonry surfaces against erosion and dust.

### COLOURS AND GLOSS

- Clear
- Gloss

### BASIC DATA

- **Surface Dry** One (1) hour
- **Recoat** Two (2) hours ( Allow 24 hours drying time on areas subject to car traffic such as car, such as driveways and garage floors).  
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** up to 5-10 M<sup>2</sup>/L (depending on the texture, surface porosity and method of application).
- **Wet Film Thickness** 83 microns
- **Dry Film Thickness** 17 microns
- **Thinning** If required, thin first coat only with 10% Estapol Gloss Slate Finish Thinner.
- **Clean up** Thoroughly clean equipment with Estapol Gloss Slate Finish Thinner.

### RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Suitable for use on a variety of surfaces including stencilled or stamped concrete, exposed aggregate, pebble finishes, brick, sandstone and other decorative surfaces.
- Ideal for bathrooms, kitchens and laundry floors, foyers, patios, steps, walls, verandahs, courtyards, driveways and paths.
- **Not** suitable for use on quarry tiles, clay pavers, terracotta surfaces, rubber, vinyl, linoleum, areas exposed to salt water (e.g. salt pool surrounds), timber decking, bitumen and areas exposed to extreme heat (e.g. barbecue and fireplace surrounds).
- **Not** suitable for use on exterior surfaces where ground water is likely to rise through the substrate.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 5°C or above 35°C. The temperature must not fall below 5°C during the drying process.
- Ensure the surface is thoroughly dry and free from dirt, grease, wax, efflorescence (white salts), moss, dust, mould or any loose material.
- New concrete surfaces should be allowed to cure 4-6 weeks. All cracks or damaged areas should be repaired. Smooth steel trowelled concrete surfaces should be acid etched to ensure maximum adhesion. Allow new grouting to dry for at least two weeks prior to coating.
- **Do not** apply in hot windy conditions.

### INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Using a quality brush or lambswool roller apply one (1) coat to most surfaces, for high traffic areas, or very porous surfaces a second coat is recommended.

**SAFETY PRECAUTIONS**

- **Caution** Flammable  
Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**  
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).  
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.  
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.  
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

**ADDITIONAL DATA**

- Available in 20 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:  
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.